

Übersichtsmatrix

UIC Leitungen

Overview array

UIC Cables

Seite		174	176	178	180	Page	
Produkt		BETAtrans® UIC C-flex R 18-adrig BETAtrans® UIC C-flex R 18 core	BETAtrans® UIC C-flex R 16-adrig BETAtrans® UIC C-flex R 16 core	BETAtrans® UIC flex 11-adrig BETAtrans® UIC flex 11 core	BETAtrans® UIC flex 9-adrig BETAtrans® UIC flex 9 core	Product	
Anwendung	Fest verlegt	■	■	■	■	Fixed installed	Application
Nennspannung	U ₀ /U	600/1000 V	■	■	■	600/1000 V	U ₀ /U Voltage range
Max. Leitertemperatur		+90 °C	■	■	■	+90 °C	Max. conductor temperature
Min. Umgebungstemperatur	Fest verlegt	-40 °C	■		■	-40 °C	Fixed installed Min. ambient temperature
		-50 °C		■		-50 °C	
Brandschutzeigenschaften	EN 45545-2	■	■	■	■	EN 45545-2	Fire performance
	EN 50264-1	■	■	■	■	EN 50264-1	

Datenblatt mit technischen Angaben auf Anfrage
Data sheet with technical data available on request

■ Gemäß Norm
In accordance to standard